

CRASH RATED TYRE KILLER – D100

Swaraj Secutech's tyre killer is a Third Generation tyre killer whose unique design combines a Fail-Safe Puncture tool and a metallurgy of hardened carbon steel which deflates even third generation run flat tyres (tube-less) effortlessly.

The Spikes have been designed to ensure that tyres of intruding vehicles are punctured irrespective of the direction of approach. It has been crash tested at Horiba, MIRA, U.K. wherein all 6 tyres of a 7.2 ton truck were deflated instatenously.

Special care is taken to ensure that the design encompasses the provision of drainage so that accumulated dirt and water can drain out instead of blocking the tyre killer mechanism. Inbuilt hydraulic hand pump gives the flexibility to use the device manually incase of power failure and secure the entrance.

Crash test pictures at MIRA, UK



Pre-Test



Post Test : All tyres deflated immediately



1218434-007

Commercial in Confidence Test Summary

SWJ-TYRE KILLER

Manufacturer: Swaraj Securtech PVT LTD
Survey No.427 RajpurJullasan Rd
Ahmedabad 382705

MIRA Contact: HSPI
Safety Development Dept
HORIBA-MIRA Ltd
Watling Street, Nuneaton
Warwickshire, CV10 0TU

Amilava@swarajsecutech.com

Test Ref: W0002 Test Date(s): 10th January 2019

This test was Not UKAS Accredited and is not included in the UKAS Accreditation Schedule for this laboratory. Opinions and interpretations expressed herein are outside the scope of HORIBA MIRA Ltd HSPi Test Centre UKAS Accreditation

Test Item(s)

Item Reference	SWJ-TYRE KILLER
Item description	Steel spiked hydraulic raising tyre killer
Item Height (mm)	150 (spikes above ground)
Item Length (mm)	4310
Foundation depth/Length (mm)	350/4912.5
Installation Date	20/12/2018
Concrete	34.7 N/mm ²
Vehicle	Iveco Eurocargo FJ09 ABN

Test Parameters

	Driven Test Requirement	Measured Value
Test Vehicle	N2A	N2A
Test Mass (kg)	7200 ± 400	7240
Impact Speed (km/h)	32.0 +3/-1	35*
Impact Angle (deg)	90.0 ± 2.0	Not Assessed
Alignment	Centerline	Not Assessed
Equipment orientation	90° From closed	90°

*Using Tacho calibrated speedometer

Test Results Summary

The Swaraj SWJ-Tyre Killer was tested at MIRA Ltd on 10th January 2019. The test was conducted at HORIBA-MIRA test location in the UK. The vehicle was driven at a speed of 35km/h over the installed system by a test engineer. The test was witnessed and filmed by HORIBA-MIRA. All tyres were punctured as intended and the vehicle brought to a controlled halt by the driver.

Prepared By:

Approved By:




Error! Unknown document property name.

Error! Unknown document property name.

Error! Unknown document property name.

Error! Unknown document property name.

Date: 17th January 2019

© HORIBA MIRA Ltd 2019. All rights reserved, subject to client contract. Information contained in this document may not be published in any form of advertising or other matter without prior agreement of the CEO of HORIBA MIRA.
HORIBA MIRA Ltd. Registered Office: Watling Street - Nuneaton - Warwickshire - CV10 0TU - England | <http://www.horiba-mira.com>
Tel: +44 (0)24 7635 5000 - Fax: +44 (0)24 7635 8000 Registered in England No 9626352 - VAT Registration GB 100 1464 84

SPECIFICATIONS

SL. NO.	DESCRIPTION	SPECIFICATIONS
1	MODEL NAME/NUMBER	D100H (HYDRAULIC)/D100M (ELECTRO-MECHANICAL)
2	SYSTEM TYPE	ACTIVE 2-WAY SPIKES
3	MECHANISM	ELECTRO-HYDRAULIC/ELECTRO-MECHANICAL
4	SPEED	3 SECOND (CUSTOMIZABLE)
5	HEIGHT OF SPIKE ABOVE THE GROUND	150 MM - 200 MM (CUSTOMIZABLE)
6	DISTANCE BETWEEN SPIKES	100 MM
7	BLOCKING ANGLE	90 DEGREE OR 60 DEGREE (CUSTOMIZABLE)
8	HOUSING	GALVANIZED MILD STEEL BODY WITH RAL COATING
9	SPIKE MATERIAL	HIGH TENSILE CARBON STEEL
10	VEHICLE LOAD	50 TON
11	SAFETY DEVICES	SAFETY AGAINST VEHICLE: LOOP DETECTOR SAFETY AGAINST HUMAN: PHOTO SENSOR
12	IP RATING	IP 66 (CUSTOMIZABLE)
13	MTBF (MEAN TIME BEFORE FAILURE)	10 MILLION OPERATIONS
14	POWER SUPPLY	230 VAC, 50 Hz/415 VAC 50 Hz
15	DUTY CYCLE	100%
16	OPERATIVE MODES	PUSH BUTTON, ACCESS CONTROL, REMOTE CONTROL
17	OPERATING TEMPERATURE	-20 °C TO +70 °C
18	POWER FAILURE MODE	MANUAL OPERATION AVAILABLE
19	CERTIFICATIONS	Crash report from Horiba Mira, UK; ISO 9001 : 2015 ; CE

"PROUDLY MADE IN INDIA"