

S8 BOLLARD

Swaraj Secutech presents Asia's first M40/ K8 bollard that has been singularly impact tested in accordance to IWA 14-1:2013 by HORIBA MIRA, UK. The bollard was hit by a fully laden 7.2-ton truck at 64 km/h which resulted in complete dead stop of the vehicle and P1 penetration. Further the bollard remained fully operational after impact.

S8 bollard has been manufactured keeping in mind the corrosive nature of the tropical climate. All parts of bollards are galvanised to prevent corrosion and smooth functioning even when submerged in water. To give a fine balance between aesthetics and security, all bollards optionally come with an aesthetically pleasing stainless steel sleeve and LED top plate that easily merges with the environment.



SAFETY

Safety is most important to us and we provide dual safety mechanism:

- Safety against vehicle: Loop Detector
- Safety against human traffic: Photo Sensor

CONTROL UNIT

Customisable External HPU or Integrated Sabotage Proof HPU along with Plc based control unit can be tailor made to the customer's requirement . It is ready to be integrated to all access control devices.

INDIA

Survey No. 1427, Chhatral-Mehsana Highway, Rajpur Jhulasan Road, Dharpura Chokdi, Jhulasan- 382705, Ahmedabad.

(T) +91 88826 64055,

Email - info@swarajsecutech.com,

Website: www.swarajsecutech.com

UAE

Swaraj Secutech Equipment & Machinery Trading LLC,

Warehouse-1, Plot No 1228. Sector 5, New Industrial

Area, Umm Al Thaoob, UAQ, UAE (T) +971 508641797,

Email: rashid@swarajsecutech.com

Website: www.swaraj.ae

NORTH AMERICA

Swaraj Secutech Canada INC

2300 Yonge street, 1600, Toronto, ON, M4P 1E4

(T) +1 (647) 242-6738

Email: mona@swarajsecutech.com,

TECHNICAL SPECIFICATIONS

MODEL NO.	S8 (1000)
DRIVE UNIT	HYDRAULIC
CYLINDER DIAMETER	270 MM / 275 MM(SS SLEEVED)
CYLINDER LENGTH	1000 MM
CYLINDER MATERIAL	HIGH TENSILE CARBON STEEL
RATING	IWA 14:2013 BOLLARD V/7200 [N2A] /64/90:1
IMPACT LOAD	7.2 TON @ 64 KMPH WITH 1M DYNAMIC PENETRATION (P1)
RAISING & LOWERING TIME	5-6 SEC. (CUSTOMISABLE)
EMERGENCY FAST OPERATION	2 SEC. (OPTIONAL AND CUSTOMISABLE)
POWER SUPPLY	415 V (AC), 50 HZ / 220V AC , 60HZ
PROTECTION CLASS	IP 68
DUTY CYCLE	100%
OPERATING TEMPERATURE	-30 DEG. CELSIUS TO +65 DEG. CELSIUS
ILLUMINATION	RED LED / REFLECTIVE BANDS
FINISH	RAL PAINTED OR SS 304/316 (Optional) SLEEVE
MTBF	50,00,000
MANUAL LOWERING OPERATIONS	AVAILABLE
SAFETY FOR VEHICLE	LOOP DETECTOR
SAFETY FOR HUMAN TRAFFIC	PHOTO SENSOR
CONTROL UNIT	PLC BASED CONTROL UNIT WITH TAILOR MADE INTEGRATION WITH ALL ACCESS CONTROL DEVICES



P1 PENETRATION



OPERATIONAL AFTER IMPACT

“PROUDLY MADE IN INDIA”

INDIA

Survey No. 1427, Chhatral-Mehsana Highway, Rajpur Jhulasan Road, Dharpura Chokdi, Jhulasan- 382705, Ahmedabad.
(T) +91 88826 64055,
Email - info@swarajsecutech.com,
Website: www.swarajsecutech.com

UAE

Swaraj Secutech Equipment & Machinery Trading LLC,
Warehouse-1, Plot No 1228. Sector 5, New Industrial Area, Umm Al Thaab, UAQ, UAE (T) +971 508641797,
Email: rashid@swarajsecutech.com
Website: www.swaraj.ae

NORTH AMERICA

Swaraj Secutech Canada INC
2300 Yonge street, 1600, Toronto, ON, M4P 1E4
(T) +1 (647) 242-6738
Email: mona@swarajsecutech.com,